



SPECIFICATIONS

Capacity: 40,000 lbs. **Trailer Weight:** 8,380 lbs.

Deck Width	8 ft. 6 in. Length: 19 ft. Height: 34 in.
Frame	Mainrails: W14" x 22 lbs. wide flange I-Beam, one piece cold formed Hi-tensile 50,000 P.S.I. steel mainrails from front to drawbar to rear of trailer 8° Beaver Tail (Safe Low Loading Angle)
Crossmembers	6" x 3.7 lbs. per ft. I-Beam pierced through mainbeam
Decking	Nominal 2" Hardwood
Headboard	8" high, full width of trailer Drawbar Storage Area
Lights	Sealed L.E.D., 12 volt, DOT approved
Wiring Harness	USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug
Hitch	One piece solid cast steel (adjustable) lunette eye & flange mount
Safety Chains	Two 1/2" Blue-Krome plated high test, safety hook w/ latch
Parking Jack	70,000 lbs. static / 40,000 lbs. lift (Heavy Duty 2-speed screw type)
Tie Down	Five per side - Patented "ROTO RINGS"® Swivel 360°
Colors	Black, Yellow, Blue (standard)

RUNNING GEAR

Tires	Eight (8) 215/75R 17.5 (H) Steel Belted Radial
Hubs/Wheels	Four Disc Type Hubs, Eight 6.75 x 17.5, 8-Bolt, Hub-Piloted Disc Wheels
Suspension	Hutch H-9700, Three leaf, capacity 50,000 lbs. tandem
Axles	Two 5" diameter 22,500 lbs. each, H.M. series bearings (maximum axle track width)
ALL WHEEL ABS	Anti-Lock Brake System 4S2M Sensor All Wheels Two Modular Valves
Parking Brake	Spring Brake on All Axles

OPTIONS

Additional Deck Length & Width (20'-21'-22'-23'-24' Optional Lengths) (96" Optional Width) Additional "ROTO-RINGS"®

Tool Box Lid (Lockable)& Optional: Expanded Metal Tray Plate

Spare Tire & Rim 215/75R 17.5 (H) Optional: Spare Tire Carrier

Traction 2" x2" Angle 6" C/C Wheel Paths Optional: Traction Center Section, Bucket Pocket or Plate

Ramps Wood (standard); Ladder (Optional N/C); Electric-Hydraulic 36" Wide x 8' Long

Extension Ramps T-6 Alum. 22" x 75" 8-degree angle (SET)

Parking Jack Optional: Jack mounted on Headboard

Apitong Decking in lieu of Oak

Paint (other than standard Black, Yellow, Blue) Price on Request

